



On-Off 60Hz

Features: ☐ Standard ☐ Optional



Auto



LED Display



Dry Mode



Comfortable
Sleeping Mode



24-hour
Timer



Self-Diagnosis



X-Fan



Auto Restart



Easy
Roll Casters



Multi-functional
Filters



Vertical Auto
Swing



AIRE
ACONDICIONADO
PORTÁTIL ECOLÓGICO

G 61



 **MEGAFRIO**
CORPORACIÓN
Especialistas en HVAC&R

Model			GPC10AP-A6NNA1C	GPC12AP-D6NNA1A
Power supply		V-Ph-Hz	110V,1Ph,60Hz	220-230V,1Ph,60Hz
Cooling (Standard conditions)	Capacity	Btu/h	10000	12010
	Input	W	975	1080
	Current	A	9,00	5,00
	EER	(Btu/h)/W	10,24	11,1
Heating (Standard conditions)	Capacity	Btu/h	/	/
	Input	W	/	/
	Current	A	/	/
	COP	W/W	/	/
Rated Power Input		W	1200	1425
Rated Current		A	11	6,6
Compressor	Model		QXF-N083xD130	QXF-A092rD130
	Type		ROTARY	ROTARY
	Brand		GREE	GREE
	Input	W	790	835
	Rated current(RLA)	A	5,98	3,88
	Locked rotor Amp(LRA)	A	47	23,5
	Refrigerant oil	ml	68SL or equivalent	68SL or equivalent
Fan Motor	Output	W	50	75
	Rated current(RLA)	A	1,2	0,65
	Capacitor	uF	10	2,5
	Speed(Hi/Mi/Lo)	r/min	1300/1200/1100	1310/1155/1030
Air flow (Hi/Mi/Lo)		m3/h	270/260/240	280/260/240
Sound pressure level (Hi/Mi/Lo)		dB(A)	54/53/51	55/53/51
Dimensions	Dimension(W*D*H)	mm	286x320x700	286x320x700
	Packing (W*D*H)	mm	358x386x876	331x396x876
	Net/Gross weight	kg	21/25.5	22.5/27
Refrigerant type/Refrigerant Charge		kg	R32/0.21	R32/0.28
Maximum Allowable Pressure		MPa	5,30	4,30
Refrigerant piping	Liquid side/ Gas side	mm	5mm/7mm	5mm/7mm
Connection wiring			AWG14#x3//	AWG18#x3//
Thermostat type			(Remote Control)	(Remote Control)
Operation temperature		°C	16~30//	16~30//
Room temperature	Indoor(cooling/ heating)	°C	16~30//	16~30//
Application area (Cooling Standard)		m²	13~19	16~24
Qty'per 20' /40' /40'HQ			192/396/592	202/416/622

INCLUYE KIT DE
INSTALACIÓN

